

YAESU KEIKOGYO CO., LTD.

Yaesu



General Catalogue

— Tape Dispenser —

— Label Dispenser —

— Film Dispenser —

ZCUT SERIES

Tape Dispenser

New Additional Function.
New Evolutionary Model.

ZCUT-9GR

ZCUT-9GR



Specifications

Cutting Length	5-999mm
Tape Width	6-60mm
Tape Thickness	0.05-0.3mm
Usable Tapes	Craft, PP, Vinyl, Filament, Glass Cloth, Double-Sided, Strapping, Protective Film, Aluminum Foil and Others
Feeding Speed	220mm/sec. Approximately 50pcs/min. (in the case of cutting 100mm with craft tape)
Max. Roll Diameter	300mm
Accessories	Separator, Blade Oil, Guide Plate, Power Cord
Body Material	ABS
Rated Voltage	AC 100-240V 50/60Hz 25W 2A Fuse (Built-In Inlet)
Dimension	116(W) × 140(H) × 213(D)mm
Weight	1.6kg

- ※ Some of usable tapes may not cut as depends on the material and tape brand.
- ※ Cutting length may be beyond cutting tolerance as depends on the type of tapes.
- ※ Specifications are subject to change without prior notice.



Easy to take maintenance.



Remove Roller Unit without using any tools.



Assist Stand to lower angle of tape feeding.



Programming Function

Six different lengths can be programmed for cutting.

Features

01	Programming Function	02	Six different lengths can be programmed for cutting.	03	Easy to take maintenance.	04	Remove Roller Unit without using any tools.
05	Preset Mode Loop Mode	P-MODE (Preset Mode) : The machine is able to be programmed. A signal will be shown based on your selected quantity of pieces and it will all cut out.		L-MODE (Loop Mode) : You can preset the quantity of piece which will be cut out. The machine will cut out the pieces based on your selected quantities then it will stop.			

OPTION

Only supply with ZCUT-9GR.



ZCUT-9GRRP

Cut a tape with backing paper while removing it.



Arm Stand

Model	Cutting Length	Tape Width	Max. Roll Diameter	Rated Voltage	Dimension	Weight
ZCUT-9GR	5-999mm	6-60mm	300mm	AC 100-240V 50/60Hz 25W	116(W) × 140(H) × 213(D)mm	1.6kg
ZCUT-9GRRP	5-999mm	6-60mm	150mm (Internal diameter 75mm)	AC 100-240V 50/60Hz 25W	116(W) × 302(H) × 320(D)mm	3.3kg

ZCUT SERIES

Tape Dispenser

Tape Dispenser with
Edge Folding Function.

ZCUT-10


Specifications

Cutting Length	5-999mm (folding 15~999mm)
Folding Length	7mm
Tape Width	6-60mm
Max. Roll Diameter	300mm
Tape Thickness	0.05-0.3mm
Usable Tapes	Craft, PP, Filament, Glass Cloth, Double-Sided, Strapping, Protective Film, Aluminum Foil and Others
Feeding Speed	220mm/sec. Approximately 50pcs/min. (in the case of cutting 100mm with craft tape)
Accessories	Separator, Blade Oil, Guide Plate, Power Cord
Rated Voltage	AC 100-240V 50/60Hz 25W 2A Fuse (Built-In Inlet)
Dimension	116(W) × 148(H) × 222(D)mm
Weight	1.83kg

- ※ Some of usable tapes may not cut as depends on the material and tape brand.
- ※ Cutting length may be beyond cutting tolerance as depends on the type of tapes.
- ※ Specifications are subject to change without prior notice.



Easy to change the function for folding and normal cutting.



Example



Folding a tape edge and easy to remove.

Usage for temporary fixing.

Features

- 01 **Memory Function**
(Six different lengths can be memorized)
- 02 **Programing Function**
(Six different lengths can be programmed for cutting)
- 03 **Two roll tapes can be cut at the same time due to Dual Photo Sensor.**
- 04 **A cut piece of tape is positioned to take out.**
- 05 **Set a tape without using bobbin.**
- 06 **Non-adhesive tapes can be cut.**
- 07 **Build-in Separator for cutting two rolls tape, Guide Plate and Blade Oil.**

OPTION

Only supply with ZCUT-10.



ZCUT-10RP

Cut a tape with backing paper while removing it.



Arm Stand

Model	Cutting Length	Tape Width	Max. Roll Diameter	Rated Voltage	Dimension	Weight
ZCUT-10	5-999mm (folding 15~999mm)	6-60mm	300mm	AC 100-240V 50/60Hz 25W	116(W)×148(H)×222(D)mm	1.83kg
ZCUT-10RP	5-999mm (folding 15~999mm)	6-60mm	150mm (Internal diameter 75mm)	AC 100-240V 50/60Hz 25W	116(W)×302(H)×330(D)mm	3.5kg

ZCUT SERIES

Tape Dispenser

Evolutionary Turntable
Type of Tape Dispenser.

ZCUT-870

Specifications

Cutting Length	15-70mm
Tape Width	3-25mm
Max. Roll Diameter	150mm
Rated Voltage	AC 100V/120V/220-240V 50/60Hz 25W
Dimension	126(W) × 150(H) × 258(D)mm
Weight	1.9kg

※ Please inform country of destination before purchasing.



ZCUT-870



Customized machine for Security Tape is available.



Polyimide Tape



Filament tape



* Scale is on the knob as a guide.

Features

01 Automatic Tape Cutting Machine reduces waste and good for environment.

02 Movable Sensor can be set at the place where Turntable stops.

03 Increase Productivity for your taping jobs.

Setting the Mode

SENSOR MODE A

When the tape reach over the movable sensor, machine will stop cutting. Remove the tape for Re-Start automatically.

SENSOR MODE B

When the tape reach over the movable sensor, machine will stop cutting. Press Start Button for Re-Start.

PRESET MODE

Stop after cutting preset number. Press Start Button for Re-Start. Maximum set number of cut is 15 pieces.

ZCUT SERIES

Tape Dispenser

Apply on different kinds of industry and tapes.

ZCUT-3EX/3EXRP

Specifications

ZCUT-3EX

Cutting Length	30-7000mm (When in manual use) 100-7000mm (When in auto use)
Tape Width	15-80mm
Max. Roll Diameter	240mm
Rated Voltage	AC 100-240V 50/60Hz 45W
Dimension	191(W) × 302(H) × 247(D)mm
Weight	9.5kg

ZCUT-3EXRP

Cutting Length	30-7000mm (When in manual use) 100-7000mm (When in auto use)
Tape Width	15-80mm
Max. Roll Diameter	150mm (Internal diameter 75mm)
Rated Voltage	AC 100-240V 50/60Hz 45W
Dimension	191(W) × 456(H) × 344(D)mm
Weight	10.5kg

ZCUT-3EX



ZCUT-3EXRP



RP Unit
For removing backing paper of double-sided tape

Features

- 01 The latest cutting method improves cutting styles.
- 02 Using L type blade of utility knife which is easy to get.
- 03 Tape feeding speed-up provides better work efficiency. Possible to cut max. 68 tapes/min. when craft tape is set with cutting length 100mm.

Adjust the width range in accordance with the selected tape (150mm · 250mm)

ZCUT-3150/3250

Specifications

ZCUT-3150

Cutting Length	40-9999mm
Tape Width	15-150mm
Max. Roll Diameter	200mm (Include Stand 400mm)
Rated Voltage	AC 100V/120V/220-240V 50/60Hz 600W
Dimension	332(W) × 298(H) × 247(D)mm
Weight	16kg

ZCUT-3250

Cutting Length	40-9999mm
Tape Width	15-250mm
Max. Roll Diameter	200mm (Include Stand 400mm)
Rated Voltage	AC 100V/120V/220-240V 50/60Hz 600W
Dimension	432(W) × 298(H) × 247(D)mm
Weight	18kg

ZCUT-3150

ZCUT-3250



ZCUT-3150 and ZCUT-3250 are using saw blade. Cutting edge is not 100% straight (little bit waving).

※ Power Voltage is maximum power dissipation when cutting (ZCUT-3150 and ZCUT-3250).
※ Please inform country of destination before purchasing.

Features

- 01 Durable for 24 hours operation.
- 02 Apply on Protection Film, Aluminum Foil and non-adhesive tapes.
- 03 Modify as depends on what kind of tape you use.

XCUT SERIES

Tape Dispenser

Double-sided adhesive tape is usable.
The construction of a new scissor cutting
can apply on non-woven tapes.

XCUT-100

Specifications

XCUT-100

Cutting Length	30-9999mm (When in manual use) 80-9999mm (When in auto use)
Tape Width	20-100mm
Feeding Speed	48pcs/min. (Craft tape in 100mm cutting length) 240mm/Sec. (Craft tape)
Max. Roll Diameter	200mm
Rated Voltage	AC 100-240V 50/60Hz 45W
Dimension	279(W) × 266(H) × 241(D)mm
Weight	11kg (Excluding Bobbin)

XCUT-100



XCUT-100RP is available to peel
backing paper during operation.

Straight Cut Edge, Designed for
low noise and less vibration.

XCUT-150/300

Specifications

XCUT-150

Cutting Length	30-9999mm (When in manual use) 60-9999mm (When in auto use)
Tape Width	20-150mm
Feeding Speed	72pcs/min. (Craft tape in 100mm cutting length) 330mm/Sec. (Craft tape)
Max. Roll Diameter	200mm
Rated Voltage	AC 100V-240V 50/60Hz 45W
Dimension	292(W) × 276(H) × 239(D)mm
Weight	9.7kg (Excluding Bobbin)

XCUT-300

Cutting Length	30-9999mm (When in manual use) 100-9999mm (When in auto use)
Tape Width	50-300mm
Feeding Speed	55pcs/min. (Craft tape in 100mm cutting length) 250mm/Sec. (In the case of craft tape)
Max. Roll Diameter	200mm
Rated Voltage	AC 100V-240V 50/60Hz 45W
Dimension	435(W) × 348(H) × 323(D)mm
Weight	17kg (Excluding Bobbin)

XCUT-150

XCUT-300



Example of Customized Belt



■ Panel Display

Confirm the cutting length.

OPTION



Exclusive footstool
for XCUT-150

Features

01 Memory Function
(3 digital: 6 memories,
4 digital: 1 memory)

02 Preset Counter
Loop Function

03 Memorize the number of
the present cutting pieces.

04 Auto feeding that cutting
tape is ready to remove after
taking the piece of tape.

Y CUT SERIES

Tape Dispenser

New style technology for wider protective tapes and films.

Y CUT-300

Specifications

Y CUT-300

Cutting Length	50-7000mm (When in manual use) 100-7000mm (When in auto use)
Tape Width	100-300mm
Max. Roll Diameter	200mm
Feeding Speed	250mm/Sec. (Protective Film) 29pcs/min. (Protective Film in 100mm cutting length)
Rated Voltage	AC100-240V 50/60Hz 45W
Dimension	520(W) × 465(H) × 175(D)mm
Weight	21kg (Excluding Bobbin)



※Above image is Y CUT-500.

Features

01

Memory Function

(3 digital: 6 memories, 4 digital: 1 memory)

02

Tape width is 300mm max.

03

Compact body.
Depth is only 175mm.

New style technology for wider protective tapes and films.

Y CUT-500

Specifications

Y CUT-500

Cutting Length	50-7000mm (When in manual use) 100-7000mm (When in auto use)
Tape Width	100-500mm
Max. Roll Diameter	200mm
Feeding Speed	250mm/Sec. (Protective Film) 29pcs/min. (Protective Film in 100mm cutting length)
Rated Voltage	AC100V-240V 50/60Hz 45W
Dimension	720(W) × 465(H) × 175(D)mm
Weight	26kg (Excluding Bobbin)



Features

01

Memory Function

(3 digital: 6 memories, 4 digital: 1 memory)

02

Tape width is 500mm max.

03

Compact body.
Depth is only 175mm.

Specification Table for Tape Dispensers


Model	Cutting Length	Tape Width	Max. Roll Diameter	Rated Voltage	Dimension	Weight
ZCUT-9GR	5-999mm	6-60mm	300mm	AC 100-240V 50/60Hz 25W	116(W)×140(H)×213(D)mm	1.6kg
ZCUT-9GRRP	5-999mm	6-60mm	150mm (Internal diameter 75mm)	AC 100-240V 50/60Hz 25W	116(W)×302(H)×320(D)mm	3.3kg
ZCUT-10	5-999mm (folding 15~999mm)	6-60mm	300mm	AC 100-240V 50/60Hz 25W	116(W)×148(H)×222(D)mm	1.83kg
ZCUT-10RP	5-999mm (folding 15~999mm)	6-60mm	150mm (Internal diameter 75mm)	AC 100-240V 50/60Hz 25W	116(W)×302(H)×330(D)mm	3.5kg
ZCUT-870	15-70mm	3-25mm	150mm	AC 100V/120V/220-240V 50/60Hz 25W	126(W)×150(H)×258(D)mm	1.9kg
ZCUT-3EX	30-7000mm (When in manual use) 100-7000mm (When in auto use)	15-80mm	240mm	AC 100-240V 50/60Hz 45W	191(W)×302(H)×247(D)mm	9.5kg
ZCUT-3EXRP	30-7000mm (When in manual use) 100-7000mm (When in auto use)	15-80mm	150mm (Internal diameter 75mm)	AC 100-240V 50/60Hz 45W	191(W)×456(H)×344(D)mm	10.5kg
ZCUT-3150	40-9999mm	15-150mm	200mm (Include Stand 400mm)	AC 100V/120V/220-240V 50/60Hz 600W	332(W)×298(H)×247(D)mm	16kg
ZCUT-3250	40-9999mm	15-250mm	200mm (Include Stand 400mm)	AC 100V/120V/220-240V 50/60Hz 600W	432(W)×298(H)×247(D)mm	18kg
XCUT-100	30-9999mm (When in manual use) 80-9999mm (When in auto use)	20-100mm	200mm	AC 100-240V 50/60Hz 45W	279(W)×266(H)×241(D)mm	11kg (Excluding Bobbin)
XCUT-150	30-9999mm (When in manual use) 60-9999mm (When in auto use)	20-150mm	200mm	AC 100-240V 50/60Hz 45W	292(W)×276(H)×239(D)mm	9.7kg (Excluding Bobbin)
XCUT-300	30-9999mm (When in manual use) 100-9999mm (When in auto use)	50-300mm	200mm	AC 100-240V 50/60Hz 45W	435(W)×348(H)×323(D)mm	17kg (Excluding Bobbin)
YCUT-300	50-7000mm (When in manual use) 100-7000mm (When in auto use)	100-300mm	200mm	AC100-240V 50/60Hz 45W	520(W)×465(H)×175(D)mm	21kg (Excluding Bobbin)
YCUT-500	50-7000mm (When in manual use) 100-7000mm (When in auto use)	100-500mm	200mm	AC100-240V 50/60Hz 45W	720(W)×465(H)×175(D)mm	26kg (Excluding Bobbin)

- ※ Some of usable tapes may not be cut as depends on tape manufacturer.
- ※ Specifications are subject to change without prior notice.
- ※ Cutting length may not be within tolerance as depends on tape material.
- ※ Stand is all optional extra.
- ※ Power Voltage is maximum power dissipation when cutting (ZCUT-3150 and ZCUT-3250).
- ※ Please inform country of destination before purchasing (ZCUT-870, ZCUT-3150 and ZCUT-3250).

CUSTOMIZED PRODUCTS

Examples

For any inquiry of modified or customized machine, please contact us.



LDX SERIES

Label Dispenser

Operability is the first priority.
Compact / Save Energy.

LDX-60

LDX-120

LDX-180

Specifications

LDX-60

Label Usable Width	15-60mm
Label Length	10-999mm
Feeding Speed	100 ~ 200mm/Sec. (Speed setting by 6 levels)
Max. Roll Diameter	200mm
Rated Voltage	AC 100V/120V/220-240V 50/60Hz 40W
Dimension	104(W) × 140(H) × 215(D)mm
Weight	2.1kg


LDX-120

Label Usable Width	15-120mm
Label Length	10-999mm
Feeding Speed	100 ~ 200mm/Sec. (Speed setting by 6 levels)
Max. Roll Diameter	250mm
Rated Voltage	AC 100V/120V/220-240V 50/60Hz 45W
Dimension	164(W) × 157(H) × 231(D)mm
Weight	3.3kg

LDX-180

Label Usable Width	15-180mm
Label Length	10-999mm
Feeding Speed	100 ~ 200mm/Sec. (Speed setting by 6 levels)
Max. Roll Diameter	300mm
Rated Voltage	AC 100V/120V/220-240V 50/60Hz 50W
Dimension	224(W) × 157(H) × 241(D)mm
Weight	4.6kg

※ Specifications are subject to change without prior notice.
※ Please inform country of destination before purchasing.



LDX-60

No scattering of backing paper.
Easy to remove label roll.



LDX-120



LDX-180

Features

01

Bobbin-less Label Dispensers.

02

C-mode, to count the number of label dispensed.

03

P-mode, to set up the number of label you need.

04

It is possible to set up the feeding speed by 6 different levels.

05

Usable label length is from 10mm(min.) to 999mm(max.)

FD SERIES

Film Dispenser

Cut OPP rolled film into various sizes of lengths with high speed.

FD-160III
FD-200III
FD-300

Specifications

FD-160III (with Film Holder)

Cutting Length	20-9999mm
Film Width	160mm
Max. Roll Diameter	210mm
Rated Voltage	AC 100-240V 50/60Hz 25W
Dimension	292(W) × 273(H) × 232(D)mm
Weight	10.6kg

FD-200III (with Bobbin)

Cutting Length	20-9999mm
Film Width	200mm
Max. Roll Diameter	210mm
Rated Voltage	AC 100-240V 50/60Hz 45W
Dimension	332(W) × 273(H) × 232(D)mm
Weight	11.1kg

FD-300(with Bobbin)

Cutting Length	20-9999mm
Film Width	300mm
Max. Roll Diameter	210mm
Rated Voltage	AC 100-240V 50/60Hz 45W
Dimension	436(W) × 347(H) × 284(D)mm (Including Bobbin Stand)
Weight	17.6kg



FD-160 III
(with Film Holder)



FD-160III Film Holder
※ FD-200III and FD-300 are with Bobbin.

OPTION



Exclusive footstool for FD-160



FD-200 III
(with Bobbin)



FD-300
(with Bobbin)

Features

01 More efficiency and hygiene because other film is placed apart.

02 High speed in cutting 65pcs per minute (100mm length).

03 Stainless steel body
→ DURABLE.



Worldwide Agencies

ASIA

JAPAN
KOREA
TAIWAN
CHINA
ISRAEL
INDIA
VIETNAM
SINGAPORE
MALAYSIA
PHILIPPINES
INDONESIA
THAILAND
CAMBODIA

OCEANIA

AUSTRALIA

EUROPE

FRANCE
HUNGARY
CZECH REPUBLIC
RUSSIA
TURKEY
GERMANY
POLAND
ENGLAND
BELGIUM
SLOVAKIA
SWEDEN
ITALY
PORTUGAL

NORTH AMERICA

CANADA
U.S.A
MEXICO

SOUTH AMERICA

ARGENTINA
BRAZIL

No Products, No Mind

カタチにできない思いはない。

Contact us

Further information on products and
services now available from the Internet.

<https://yaesu1965.com/en>



YAESU KEIKOGYO CO., LTD.

39-8 Senju Motomachi, Adachi-Ku, Tokyo, 120-0041, Japan