

AUTO TAPE DISPENSER

ZCUT-3EX

| New Structure of Cutting Method

Equipped brushless motor enables maintenance-free of cutting unit.

| Possible to cut tape with the blade commercially available

Using L type blade of utility knife which is easy to get and to change as well.

| Speed and Efficiency improved

50% increased the number of cutting tape as compared with old model.

| Many useful functions are available for your taping work



Yaesu

CE

AUTO TAPE DISPENSER

ZCUT-3EX

I Features

New Structure of Cutting Method improves cutting performance

Tape glue is not easily stuck on blade edge by optimizing blade angle.
By keeping blade clean, 50% increased cutting durability as compared with old model. ※1
Low Noise, Low Vibration.

Using the blade commercially available

Using L type blade of utility knife which is low cost and easy to get.
It enables you to keep sharpness with new blade.

Tape feeding speed-up provides better work efficiency

Possible to cut max. 68 tapes/min. when craft tape is set with cutting length 100mm.
(Old model is max. 44 tapes/min.)

Tape width within 240mm is possible to set

Thick rolled tape can be set without modification.

Memory function of tape-cut length

Possible to memorize 7 different cutting length.
(6 memories within 999mm and 1 memory within 7000mm)

Preset Counter

Count-down preset numbers of tape-cut and buzzer sounds when finished.
(Loop mode, to continuously cut the preset numbers of tape, is available as well)

Auto/Manual mode is possible to select

Auto mode, to feed tape automatically after you pull out the tape, and Manual mode, to feed and cut tapes by lifting Start Switch up, are selectable.

※1 This test is done with OPP adhesive tape, and it is not applied to all types of the tapes.

* As regards customized machine, please feel free to ask us or distributors.

I Specifications

Rated Voltage	90-264 VAC 50/60Hz
Power Consumption	45 W
Dimension	191 W x 302 H x 247 D mm (excluding boss)
Weight	9.5 kg
Tape Width	15-80 mm
Cutting Length	30-7000 mm (Manual mode) 100-7000 mm (Auto mode)
Feeding Speed	330mm/sec. (craft tape) 68 tapes/min. when cut-length is set 100mm (craft tape)
Max. Outside Diameter of Roll	240mm
Accessories	Power Cord Bobbin (Φ75, Φ31) 2A Fuse (Built-in Inlet) Hexagonal Spanner Spare blade 6PCS
Usable Tapes	Craft, Cloth, PP, Vinyl, Glass Filament, Aluminum Foil and Others.

* Some of usable tapes may not cut as depends on the material and tape brand.

* Cutting length may be beyond cutting tolerance as depends on the type of tapes.

* The specifications are subject to change without prior notice.

Example of customized products

RP Unit



For removing backing paper of double-sided tape

Silicon Roller



Scratch prevention

Clutch Bobbin



For slack prevention of Non-adhesive* tape

Anti-static brush



ESD protection

● Contact us

YAESU KEIKOGYO CO., LTD.

39-8 Senju Motomachi, Adachi-Ku, Tokyo, 120-0041, Japan
Tel 81-3-3888-8751 Fax 81-3-3888-1592
<http://www.yaesu1965.com>